

TABLE OF CONTENTS

Fully Automatic Strapping Machine M-60 Series	2
Fully Automatic Strapping Machine M-60AX PB-2HT	2
Fully Automatic Strapping Machine M-60AXPB-AP-2HT	4
Fully Automatic Strapping Machine M-60AX 940D	5
Fully Automatic Strapping Machine M-60AX 940	6
Fully Automatic Strapping Machine M-60AX PR-3HT	7
Fully Automatic Strapping Machine M-60AX-900D	8
Fully Automatic Strapping Machine M-60AXPR-2HT	9
Fully Automatic Strapping Machine M-60AX-NM	10
Fully Automatic Strapping Machine M-60AX N5	11
Fully Automatic Strapping Machine M-60AXM	12
Fully Automatic Strapping Machine M-60AXN	14
Fully Automatic Strapping Machine M-60AX	16



FULLY AUTOMATIC STRAPPING MACHINE M-60 SERIES



FULLY AUTOMATIC STRAPPING MACHINE M-60AX PB-2HT

SKU: M-60AX PB-2HT

Fully Automatic Strapping Machine M-60AX PB-2HT

- Power Belt Table (with 8 timing Belts).
- Fully Automatic Strapping Machine M-60AX PB-2HT is equipped with two photocells(2HT), safely 21V, and a PLC electric control system.
- Users can choose to strap for 1 strap, 2 straps, or no strap via the control panel, depending on the user's choice.
- Supply a circuit to combine the input & output of the conveyors.
- 110/220V single-phase is available.
- Easy maintenance by the raised top cover
- Patent now aluminum arch with iron arch cover (Standard)
- The other details are as same as M-60AX

Specifications

750 x 565 mm

(Iron Arch Cover)(Standard)

Power Supply 110V/220V/1 Phase 220V380V/415V 3 Phase

Strap Cycle Speed 25-27 Cycles / Min (60 HZ)
It depends on the package size

Dimension (WxDxH) 1290 x 640 x 1470 mm (Standard)

Strap Width 6 - 15 mm

(Change kits and adjustment)

Tension Strength 5 - 75 kg **Table Height** 810 mm

Available Packing Size

(WxH)

250-500 x 30-450 mm

Net Weight 247kg

Sealing Method Heat Sealing









FULLY AUTOMATIC STRAPPING MACHINE M-60AXPB-AP-2HT

SKU: M-60AXPB-AP-2HT

Fully Automatic Strapping Machine M-60AXPB-AP-2HT

- Equipped with light-duty air pressure. (Pressure 6 kg/cm (Bar), Cylinder, inner 050 mm, Stroke 550mm)
- Fully Automatic Strapping Machine M-60AXPB-AP-2HT is suitable for strapping cartons, paper boards, or pre-transported formative cases, etc.
- According to requirements, additional functions, such as delaying the strapping, are available (Optional)
- Arch site is optional to fit various packages.
- The other details are as same as M-60AXPB-2HT

Specifications

750 x 565 mm

(Iron Arch Cover)(Standard)

Power Supply 110V/220V/1 Phase 220V380V/415V 3 Phase

Strap Cycle Speed 25-27 Cycles / Min (60 HZ)

It depends on the package size

Dimension (WxDxH) 1394 x 645 x 1615 mm (Standard)

Strap Width 6 - 15 mm

(Change kits and adjustments)

Tension Strength 5 - 75 kg **Table Height** 810 mm

Available Packing Size (WxH) 250-500 x 30-450 mm

Net Weight 323 kg

Sealing Method Heat Sealing





FULLY AUTOMATIC STRAPPING MACHINE M-60AX 940D

SKU: M-60AX 940D

Fully Automatic Strapping Machine M-60AX 940D

- 2 front doors type
- Fully Automatic Strapping Machine M-60AX 940D has a retractable coil holder for easy coil loading
- External type foot pedal switch
- Iron cover arch (Optional)
- Equipped with brushes on the top & 2 sides of the iron arch covers to fix the strapping position (Optional)

Specifications

750 x 575 mm Arch Size (WxH) (Iron Arch Cover)

Power Supply 110V/220V/1 Phase 220V380V/415V 3 Phase

30 Cycles / Min (60 HZ) **Strap Cycle Speed**

It depends on the package size

Dimension (WxDxH) ogist 940 x 640 x 1500 mm (Standard)

Strap Width

(Change kits and adjustment)

Tension Strength 5 - 75 kg **Table Height** 830 mm

100-650 x 30-450 mm **Available Packing Size**

(WxH) Iron Arch Cover

Net Weight 200 kg

Sealing Method Heat Sealing





FULLY AUTOMATIC STRAPPING MACHINE M-60AX 940

SKU: M-60AX 940

Fully Automatic Strapping Machine M-60AX 940

- Fully Automatic Strapping Machine M-60AX 940 has a retractable coil holder for easy coil loading
- Iron arch cover (Optional)

Specifications

Arch Size (WxH) 800 x 600 mm

(Aluminium Arch Cover) (Standard)

Power Supply 110V/220V/1 Phase 220V380V/415V 3 Phase

Strap Cycle Speed 30 Cycles / Min (60 HZ)

It depends on the package size

Dimension (WxDxH) 940 x 640 x 1500 mm

Strap Width

(Change kits and adjustment)

Tension Strength 5 - 75 kg **Table Height** 830 mm

Available Packing Size 100-700 x 30-500 mm (WxH) Aluminium Arch Cover

Net Weight 200 kg

Sealing Method Heat Sealing





FULLY AUTOMATIC STRAPPING MACHINE M-60AX PR-3HT

SKU: M-60AX PR-3HT

Fully Automatic Strapping Machine M-60AX PR-3HT

Power Roller Table with Big Arch 1150W x 375H mm

- Fully Automatic Strapping Machine M-60AX PR-3HT is suitable for various heavy products such as tiles, bricks, and so on
- 3 photocells Rod Yellow/Green warning lamp, and a buzzer
- Iron cover arch (Standard)
- The other deals were similar to M-60AXPB-2HL
- Brushes on the top and 2 sides of the Iron arch cover. (Optional)
- Embossed process on the power roller's surface (Optional)

Specifications

1150 x 375 mm

Arch Size (WxH) (iron Arch Cover) Standard)

Power Supply 110V/220V/1 Phase 220V380V/415V 3 Phase

Strap Cycle Speed

25-27 Cycles / Min (60 HZ)

It depends on the package size

Dimension (WxDxH) 1640 x 640 x 1285 mm

Strap Width 6 - 15 mm

(Change kits and adjustment)

Tension Strength 5 - 75 kg **Table Height** 823 mm

Available Packing Size (WxH) 250-800 x 30 250mm

Net Weight 300 kg

Sealing Method Heat Sealing





FULLY AUTOMATIC STRAPPING MACHINE M-60AX-900D

SKU: M-60AX-900D

Fully Automatic Strapping Machine M-60AX-900D

- Single front door type
- Retractable coil holder for easy coil loading
- Fixed foot pedal switch long side machine
- 900D 3 pieces of L-type carton holders on the top table to fix the strapping position
- Available for strapping money, mail, and tiny boxes, etc.
- Without any free rollers on the top table
- Iron arch cover (Optional)
- #32 tiny slide table to strap the tiny packages (Optional)
- Equipped with brushes on the top and 2 sides of the iron arch covers to fix the strapping position (Optional)

Specifications for Fully Automatic Strapping Machine M-60AX-900D

Arch Size (WxH) 760 x 400 mm (Aluminium Arch)

Power Supply 110V/220V/1 Phase 220V380V/415V 3 Phase

Strap Cycle Speed

30 Cycles / Min (60 HZ)

It depends on the package size

Dimension (WxDxH) 900 x 640 x 1300 mm

6 - 15 mm

Strap Width (Change kits and adjustments)

Tension Strength 5 - 75 kg **Table Height** 830 mm

Available Packing Size (WxH)

(with #32 tiny side table)

Net Weight 200 kg
Sealing Method Heat Sealing





FULLY AUTOMATIC STRAPPING MACHINE M-60AXPR-2HT

SKU: M-60AXPR-2HT

Fully Automatic Strapping Machine M-60AXPR-2HT

Power Roller Table with Arch 750W x575H mm (Standard)

- Power Roller Table with Arch 750W x 575H mm (Standard). Power Roller Table: It is easy to maintain by raised-up top cover.
- Equipped with two photocells (2HT), a safety 24, and a PLC electrical control system.
- The user can choose to strap for 1 strap, 2 straps, or no strap via the control panel it depending on the user's choice
- Supply a circuit to combine the input & output of the conveyors. 110W220V single-phase is available.
- The other details are as same as M-60AXPB-2HT

Specifications for Fully Automatic Strapping Machine M-60AXPR-2HT

LOGISTICS SIMPLIFIED

лск зР

750 x 575 mm

(Iron Arc Cover) (standard)

Power Supply 110V/220V/1 Phase 220V380V/415V 3 Phase

Strap Cycle Speed 25-27 Cycles / Min (60 HZ)

It depends on the package size

Dimension (WxDxH) 1240 x 650 x 1480 mm

6 - 15 mm

(Change kits and adjustments)

Tension Strength 5 - 75 kg **Table Height** 815 mm

Strap Width

Available Packing Size (WxH) 250-500 x 30-450 mm

Net Weight 247kg

Sealing Method Heat Sealing





FULLY AUTOMATIC STRAPPING MACHINE M-60AX-NM

SKU: M-60AX-NM

Fully Automatic Strapping Machine M-60AX-NM

Arch: 600W x 400H mm (Standard)

- Single front door type
- The medium size of the frame is suitable for strapping the tiny boxes, mail, newspapers, and magazines.
- Upgrade the AUTO-FEEDING system.
- To upgrade the Forwarding & Reversing System.
- The purpose is to speed up the strapping cycle.
- Each cycle is accurate and efficient. Fixed foot pedal switch long side machine
- Iron arch cover (Optional)
- The details are as same as M-60AXN

Specifications for Fully Automatic Strapping Machine M-60AX-NM

600 x 400 mm

Arch Size (WxH)

(Aluminium Arch X standard)

Power Supply 110V/220V/1 Phase 220V380V/415V 3 Phase

Strap Cycle Speed 34-36 Cycles / Min (60 HZ)

Dimension (WxDxH) 1040 x 500 x 1275 mm

Strap Width 6 - 15 mm

(Change kits and adjustments)


Tension Strength 5 - 75 kg **Table Height** 805 mm

Available Packing Size (WxH) 100-550 x 30-375 mm

Net Weight 170 kg

Sealing Method Heat Sealing





FULLY AUTOMATIC STRAPPING MACHINE M-60AX N5

SKU: M-60AX N5

Fully Automatic Strapping Machine M-60AX N5

Big Arch (1250W x 500H mm) (Iron Arch Cover) (Standard)

- Available for 5mm P.P. strap
- Movable arch bandway design
- DC business motor technology
- Speedy, stable, and low-noisy design
- Fully Automatic Strapping Machine M-60AX N5 has a retractable coil holder for easy coil leading
- Fixed foot pedal switch long side machine
- Humanized design of the control panel

Specifications

Arch Size (WxH) 250 x 500 mm (Iron Arch Cover) (Standard)

Power Supply 110V/220V/1 Phase 220V380V/415V 3 Phase

Strap Cycle Speed

Dimension (WxDxH) 1490 x 625 x 1410 mm

Strap Width5 mmTension Strength5 - 75 kgTable Height830 mm

Available Packing Size (WxH) 100-1550 x 30-450 mm

Net Weight

Sealing Method Heat Sealing





FULLY AUTOMATIC STRAPPING MACHINE M-60AXM

SKU: M-60AXM

Fully Automatic Strapping Machine M-60AXM

Arch: 600W x 400H mm (Standard)

- The medium size of frame of M 6GAX is designed to strap tiny boxes, mails, newspapers and magazines.
- It is suitable to operate in your offices, post offices and so on.
- Fully Automatic Strapping Machine M-60AXM is suitable for strapping 6 mm of strap.
- Fully Automatic Strapping Machine M-60AXM is equipped with auto feeding function, instant heater function, internal foot pedal system and low noise operation etc. The main purpose is to make the operation more easily.
- With CKD frame and powder painting on frame and iron arch cover. Powder painting is only suitable for M-60AX & M-60AXM.
- Standard color on frame (Silver) and front control panel (Pigeon Blue)
- The other details are the same as the M-60AX.

Specifications

Arch Size (WxH) 600 x 400 mm

(Aluminium Arch)

Power Supply 110V/220V/1 Phase 220V380V/415V 3 Phase

Strap Cycle Speed 34-36 Cycles / Min (60 HZ)

Dimension (WxDxH) 1040 x 500 x 1275 mm

Strap Width 6 - 15 mm

(Change kits and adjustment)

Tension Strength 5 - 75 kg **Table Height** 805 mm

Available Packing Size

(WxH) 100-550 x 30-375 mm

Net Weight 170 kg

Sealing Method Heat Sealing









FULLY AUTOMATIC STRAPPING MACHINE M-60AXN

SKU: M-60AXN

Fully Automatic Strapping Machine M-60AXN

The new M-60AXN is a modern concept of a fully automatic strapping machine with the upgrade Auto-feeding system for a dependable and reliable strapping application

- Fully Automatic Strapping Machine M-60AXN has 2 front doors type
- Upgrade the AUTO-FEEDING system to upgrade the Auto-Feeding system and the Forwarding & Roversing system. The purpose is to speed up the strapping cycle. Each cycle is accurate and efficient.
- JAM-FREE function: auto strap loops ejecting design to solve the strapping problem
- Fixed foot pedal switch long side machine
- Fully Automatic Strapping Machine M-60AXN is equipped with a
 patent aluminum alloy arch modular design: it is easy to
 assemble, disassemble, change size, economical, no arch motor is
 required (3rd Generation)
- Strep cycle can be done by a start switch, table ball switch and foot pedal ber
- Lift hype top cover allows convenient maintenance
- Iron arch cover (Optional)

Specifications

Arch Size (WxH) 800 x 600 mm

(Aluminium Arch Cover x Standard)

Power Supply 110V/220V/1 Phase 220V380V/415V 3 Phase

32-35 Cycles / Min (50 HZ)

Strap Cycle Speed It depends on the package size and special

requirements.

Dimension (WxDxH) 1240 x 625 x 1465

Strap Width

(Change kits and adjustment)

Tension Strength 5 - 75 kg **Table Height** 795 mm

Available Packing Size (WxH) 100-750 x 30-550 mm

Net Weight Approx 200 kg



Sealing Method

Heat Sealing







FULLY AUTOMATIC STRAPPING MACHINE M-60AX

SKU: M-60AX

Fully Automatic Strapping Machine M-60AX

800W X 600H mm (Aluminum Arch) (Standard)

- Innovatory AUTO-FEEDING Function: to press the "INSERT button, the strap will be fed automatically and be ready for the first strapping cycle applicao
- Auto positioning and retry function: to ensure the strap goes to its proper position, and every cycle is accurate and efficient
- JAM-FREE function auto stap loops ejecting design to correct strapping problems
- Electronic tensioning: to get optional 5-75 ky tension strength by adjusting the tension knob
- Internal foot pedal system: strap cycle will be completed more easily
- Fully Automatic Strapping Machine M-60AX is equipped with a
 patent aluminum alloy arch modular design, it is easy to
 assemble, disassemble, and change size economically; no arch
 motor is required (3rd Generation)
- A strap cycle can be done by a start switch, a label ball switch, and a foot pedal bar.
- With the motor's auto-stop function
- Fully Automatic Strapping Machine M-60AX has a lift-type top cover that allows convenient maintenance.

Specifications

Arch Size (WxH) 800 x 600 mm (Aluminium Arch)

Power Supply 110V/220V/1 Phase 220V/380V/415V 3 Phase

Strap Cycle Speed 32–35 Cycles / Min (60 HZ)

Dimension (WxDxH) 1240 x 500 x 1475mm

Strap Width 6 - 15 mm

(Change kits and adjustments)

Tension Strength 5 - 75 kg **Table Height** 805 mm

Available Packing Size (WxH) $100-750 \times 30-575 \text{ mm (Aluminium Arch)}$ $100-700 \times 30-550 \text{ mm (Iron Arch Cover)}$

Net Weight App 100 kg
Sealing Method Heat Sealing











INDEX

F

Fully Automatic Strapping Machine M-60AX 15
Fully Automatic Strapping Machine M-60AX 940 5
Fully Automatic Strapping Machine M-60AX 940D 4
Fully Automatic Strapping Machine M-60AX N5 10
Fully Automatic Strapping Machine M-60AX PB-2HT 1
Fully Automatic Strapping Machine M-60AX PR-3HT 6
Fully Automatic Strapping Machine M-60AX-900D 7
Fully Automatic Strapping Machine M-60AX-NM 9
Fully Automatic Strapping Machine M-60AXM 11
Fully Automatic Strapping Machine M-60AXN 13
Fully Automatic Strapping Machine M-60AXPB-AP-2HT 3
Fully Automatic Strapping Machine M-60AXPR-2HT 8

