



## TABLE OF CONTENTS

<b>Fully Automatic Strapping System JN-85 Series</b> .....	2
Fully Automatic Strapping System JN-85 APN .....	2
Fully Automatic Strapping System JN-85 OP .....	4
Fully Automatic Strapping System JN-85 PRAPN .....	5
Fully Automatic Strapping System JN-85 PRU .....	6
Fully Automatic Strapping System JN-85 LPBU .....	7
Fully Automatic Strapping System JN-85 PBU .....	8
Fully Automatic Strapping System JN-85 LPRU .....	9
Fully Automatic Strapping System JN-85 EM .....	10
Semi-automatic pallet strapping machine JN-85 PS .....	12
Fully Automatic Strapping System JN-85 SE .....	13
Semi-auto Pallet Strapping Machine JN-85 PSA .....	14
Fully Automatic Strapping System JN-85 ZE .....	15
Fully Automatic Strapping System JN-85 E .....	17
Fully Automatic Strapping System JN-85 PBAPN .....	19
Fully Automatic Strapping Machine - JN-85 PBTAPN .....	20



# FULLY AUTOMATIC STRAPPING SYSTEM JN-85 SERIES



## FULLY AUTOMATIC STRAPPING SYSTEM JN-85 APN

**SKU:** JN-85 APN

### Fully Automatic Strapping System JN-85 APN

#### Light-duty Air-pressure

- Mono-strapping with air-pressing bar which is suitable for carton/ paperboard or pre-transported forming-case strapping.
- The arch size is optional to fit various package sizes.
- According to requirements, Fully Automatic Strapping System JN-85 APN additional functions such as heavier pressure or delay strapping is available

#### Specifications

<b>Arch Size</b>	850W x 600H mm (Standard)
<b>Power Supply</b>	110/220V 50/60Hz 1 Phase 220/380V 50/60Hz 3 Phase
<b>Strap Cycle Speed</b>	8 Sec/Cycle
<b>Tension Strength</b>	Max. 70 kgs
<b>Sealing Method</b>	Heat Sealing
<b>Cylinder</b>	Inner Diameter; 040
<b>Pressure</b>	5 kg/cm (Bar)
<b>Stroke</b>	550mm
<b>Dimensions</b>	1450W x 640D x 2140H mm (Standard)
<b>Table Height</b>	810mm
<b>Machine Weight</b>	315 kgs
<b>Gross Weight</b>	432 kgs



**QUICK 3PL**  
LOGISTICS SIMPLIFIED

**Categories:** [Fully Automatic Strapping System JN-85 Series](#), [Strapping Machine](#)



**QUICK 3PL**  
LOGISTICS SIMPLIFIED



## FULLY AUTOMATIC STRAPPING SYSTEM JN-85 OP

**SKU:** JN-85 OP

### Fully Automatic Strapping System JN-85 OP

#### Oil-Pressure

- It is suitable to strap expensive packages such as canvas bags, dustproof bags and corrugated boards and so on.
- Fully Automatic Strapping System JN-85 OP is equipped with 5 HP Oil Compression System and with stronger external frame structure to provide 2.5 Ton of pressure.

#### Specifications

<b>Arch Size</b>	850W x 800H mm (Standard)
<b>Power Supply</b>	110/220V 50/60Hz 1 Phase 220/380V/415V 3 Phase
<b>Tension Strength</b>	Max 70 kg
<b>Strap Width</b>	9.15mm (Change kits and adjustment)
<b>Sealing Method</b>	Heat Sealing
<b>Dimensions</b>	1760W x 640D x 2700H mm (Standard)
<b>Table Height</b>	815mm
<b>Oil Cylinder</b>	050 x 750L mm per piece (2 pieces/machine)

**Categories:** [Fully Automatic Strapping System JN-85 Series](#), [Strapping Machine](#)



## FULLY AUTOMATIC STRAPPING SYSTEM JN-85 PRAPN

**SKU:** JN-85 PRAPN

### Fully Automatic Strapping System JN-85 PRAPN

#### Power Roller Table with Light-duty Air pressure

- Mono-strapping with air-pressing bar which is suitable for carton/ paperboard or pre-transported forming-case strapping.
- The arch size is optional to fit various package sizes.
- According to requirements, additional functions such as heavier pressure or delay strapping is available.
- Fully Automatic Strapping System JN-85 PRAPN is equipped with a Table Roller Cover.

### Specifications

<b>Arch Size</b>	1650W x 600H mm (Standard)
<b>Power Supply</b>	110/220V 50/60Hz 1Ph; 220/380V 50/60Hz 3 Ph;
<b>Strap Width</b>	9- 15.5mm
<b>Sealing Method</b>	Heat Sealing
<b>Cylinder</b>	Inner Diameter: 040
<b>Pressure</b>	5 kg/cm <sup>2</sup> (Bar)
<b>Stroke</b>	550mm
<b>Dimensions</b>	2350W x 800D x 2300H mm
<b>Table Height</b>	815mm

**Categories:** [Fully Automatic Strapping System JN-85 Series](#), [Strapping Machine](#)



## FULLY AUTOMATIC STRAPPING SYSTEM JN-85 PRU

**SKU:** JN-85 PRU

### Fully Automatic Strapping System JN-85 PRU

#### Standard Power Roller Table


- Standardized power roller table model with 2 sets of photocell JN-85PRU-2HT.
- Optional straps No. is available for 1, 2 or no strapping on the packages. More straps application is also available as an option before order is fixed.
- This model can incorporate input and output conveyors as a strapping system. The control system of conveyors can be connected with this model.
- An optional photocell to control the table transmitting is available, which can auto-stop the table when no package is input.
- Fully Automatic Strapping System JN-85 PRU is equipped with Table Roller Cover.

#### Specifications



<b>Arch Size</b>	850W x 600H mm (Standard)
<b>Power Supply</b>	110/220V 50/60Hz 1Ph; 220/380V 50/60Hz 3 Ph;
<b>Strap Cycle Speed</b>	2.5 Sec/cycles
<b>Tension Strength</b>	Max. 70kg
<b>Strap Width</b>	9- 15.5mm
<b>Sealing Method</b>	Heat Sealing
<b>Dimensions</b>	1550W x 800D x 1470H mm
<b>Table Height</b>	815mm
<b>Machine Weight</b>	330 kgs
<b>Gross Weight</b>	430 kgs
<b>Power Roller Speed</b>	15M/50Hz Per Min.

**Categories:** [Fully Automatic Strapping System JN-85 Series](#), [Strapping Machine](#)



## FULLY AUTOMATIC STRAPPING SYSTEM JN-85 LPBU

**SKU:** JN-85 LPBU

### Fully Automatic Strapping System JN-85 LPBU

#### Low Table Power Belt Model

- Low power belt table with standard table height H450 or H500mm. Optional height for incorporating with a conveyor is also available. (Optional)
- Fully Automatic Strapping System JN-85 LPBU is equipped with 2 sets of photocells to work with conveyors is available JN-85LPB-2HT.
- Refer to JN-85PBU for rest features

#### Specifications

<b>Arch Size</b>	850W x 600H mm (Standard)
<b>Power Supply</b>	110/220V 50/60Hz 1Ph; 220/380V 50/60Hz 3 Ph;
<b>Strap Cycle Speed</b>	2.5 Sec/cycles
<b>Tension Strength</b>	Max. 70kg
<b>Strap Width</b>	9- 15.5mm
<b>Sealing Method</b>	Heat Sealing
<b>Dimensions</b>	1940W x 640D x 1670H mm
<b>Table Height</b>	455mm or 505mm
<b>Machine Weight</b>	307 kgs
<b>Gross Weight</b>	402 kgs
<b>Power Belt Speed</b>	17M/50Hz Per Min.

**Categories:** [Fully Automatic Strapping System JN-85 Series](#), [Strapping Machine](#)



## FULLY AUTOMATIC STRAPPING SYSTEM JN-85 PBU

**SKU:** JN-85 PBU

### Fully Automatic Strapping System JN-85 PBU

#### Standard Power Belt Table

- Fully Automatic Strapping System JN-85 PBU has a standardized power belt table model with 2 sets of photocells.
- Optional straps No. is available for 1, 2 or no strapping on the packages. More straps application is also available as an option before order is fixed.
- This model can incorporate input and output conveyors as a strapping system. The control system of conveyors can be connected with this model.
- An optional photocell to control the table transmitting is available, which can auto-stop the table when no package is input.

#### Specifications



<b>Arch Size</b>	850W x 600H mm (Standard)
<b>Power Supply</b>	110/220V 50/60Hz 1Ph; 220/380V 50/60Hz 3 Ph;
<b>Strap Cycle Speed</b>	2.5 Sec/cycles
<b>Tension Strength</b>	Max. 70kg
<b>Strap Width</b>	6- 15.5mm
<b>Sealing Method</b>	Heat Sealing
<b>Dimensions</b>	1550W x 640D x 1550H mm
<b>Table Height</b>	825mm
<b>Machine Weight</b>	307 kgs
<b>Gross Weight</b>	402 kgs
<b>Power Belt Speed</b>	17M/50Hz Per Min.

**Categories:** [Fully Automatic Strapping System JN-85 Series](#), [Strapping Machine](#)



## FULLY AUTOMATIC STRAPPING SYSTEM JN-85 LPRU

**SKU:** JN-85 LPRU

**Fully Automatic Strapping System JN-85 LPRU**


### Low Table Power Roller Model

- Lower power roller table with standard table height H450 or H500mm.
- Optional height for incorporating with a conveyor is also available.(Optional)
- Fully Automatic Strapping System JN-85 LPRU is equipped with 2 photocells to work with conveyors is available JN-85LPRU-2HT.
- Refer to JN-85PRU for rest features.
- Equipped with Table Roller Cover

### Specifications

<b>Arch Size</b>	850W x 600H mm (Standard)
<b>Power Supply</b>	110/220V 50/60Hz 1Ph; 220/380V 50/60Hz 3 Ph;
<b>Strap Cycle Speed</b>	2.5 Sec/cycle
<b>Tension Strength</b>	Max. 70kg
<b>Strap Width</b>	6- 15.5mm
<b>Sealing Method</b>	Heat Sealing
<b>Dimensions</b>	1940W x 800D x 1670H mm
<b>Table Height</b>	455mm or 505mm
<b>Machine Weight</b>	307 kgs
<b>Gross Weight</b>	402 kgs
<b>Power Roller Speed</b>	15M/50Hz Per Min.

**Categories:** [Fully Automatic Strapping System JN-85 Series](#), [Strapping Machine](#)



## FULLY AUTOMATIC STRAPPING SYSTEM JN-85 EM

**SKU:** JN-85 EM

### Fully Automatic Strapping System JN-85 EM

The Fully Automatic Strapping System JN-85 EM Compact Model is designed to optimize packaging processes. This compact model not only enhances efficiency but also saves valuable space in your operational area. It's an ideal solution for businesses looking to streamline their strapping operations without compromising on performance.

### Minimized Model

In today's fast-paced industrial environment, having a minimized model can significantly improve workflow. The JN-85 EM Compact Model is particularly beneficial in factories or warehouses where space is at a premium. With its compact design, it can fit seamlessly into existing production lines, ensuring that productivity is maintained.

- Minimized model of JN-85U by width and height 200mm, Fully Automatic Strapping System JN-85 EM is suitable for smaller working space and for smaller packages strapping.

For instance, a company that relies on frequent shipping of smaller packages can benefit from the minimized model of the JN-85 EM. By utilizing this equipment, they can strap items more efficiently, thereby speeding up their packing process and reducing the risk of damage during transit.

- If a customer requires an optional size smaller than 650W x 400 Hmm is available.

Additionally, for specific industries such as e-commerce or food packaging, the option to customize the size of the JN-85 EM Compact Model less than the standard 650W x 400H mm can cater to unique packaging needs. This adaptability ensures that various product sizes can be handled with ease, maximizing operational flexibility.

- With CKD frame and powder painting on frame.

The CKD (Complete Knock Down) frame is a noteworthy feature. It allows for easy transport and assembly, making the Fully Automatic Strapping System JN-85 EM an attractive option for businesses that may need to relocate their operations or expand into new facilities. The powder painting on the frame not only enhances durability but also provides a clean, professional appearance.

- Change color on the iron arch cover, front doors & frame is



available. (Optional)

Moreover, changing the color of the iron arch cover, front doors, and frame can provide a customized touch, allowing businesses to maintain brand consistency in their equipment. This feature is often appreciated by companies looking to present a cohesive image to their clients.

### **Specifications**

Understanding the specifications is crucial for selecting the right strapping system. The Fully Automatic Strapping System JN-85 EM's arch size of 650W x 400H mm is designed to accommodate a wide range of products, making it versatile for various applications in different industries.

For example, companies in the manufacturing sector may require strapping for assembled goods, while retailers may need it for packaging retail items. The adaptability of the arch size ensures that it meets the demands of diverse packaging requirements, enhancing operational efficiency.

Furthermore, the standard arch size allows for quick adjustments and easy use, which is essential in high-volume production settings. Operators will find that the learning curve for utilizing this equipment is minimal, allowing for rapid deployment in various environments.

**Arch Size** 650W x 400H mm (Standard)

In conclusion, the Fully Automatic Strapping System JN-85 EM Compact Model stands out as a practical solution for businesses aiming to improve their packaging processes. With its minimized design, customizable options, and robust specifications, it aligns perfectly with modern operational needs. Investing in such a system not only enhances productivity but also contributes to overall business growth.


**Categories:** [Fully Automatic Strapping System JN-85 Series](#), [Strapping Machine](#)



## SEMI-AUTOMATIC PALLET STRAPPING MACHINE JN-85 PS

**SKU:** JN-85 PS

### Semi-automatic pallet strapping machine JN-85 PS



- The Semi-automatic pallet strapping machine is suitable for various packaging needs, making it a versatile choice for many industries, including logistics, manufacturing, and retail.
- Used various requirements when packaging cargo on pallets.
- Moveable design of this model provides convenient operation, especially for delicate working places with manual lifts where cranes cannot reach.
- This model's moveable design allows for flexible operations, enabling the machine to be used in tight spaces where other machinery may not fit, thereby maximizing the use of available workspace.

The Semi-automatic pallet strapping machine is an essential tool in the packaging industry, designed to optimize and streamline the process of securing goods on pallets. With growing demands for efficient packaging solutions, investing in such machinery can significantly influence productivity and operational efficiency.

The Semi-automatic pallet strapping machine is particularly designed to handle varying requirements for packaging cargo on pallets, making it adaptable for different types of goods, from fragile items that require gentle handling to heavy-duty products that need robust securing methods.

### Specifications

#### Importance of Choosing the Right Packaging Equipment

#### Benefits of Using a Semi-automatic Pallet Strapping Machine

<b>Strap Guide Length</b>	1000 mm (Standard)
<b>Min. Packaging Height</b>	550 mm

**Categories:** [Fully Automatic Strapping System JN-85 Series](#), [Strapping Machine](#)



## FULLY AUTOMATIC STRAPPING SYSTEM JN-85 SE

**SKU:** JN-85 SE

### Fully Automatic Strapping System JN-85 SE


#### Stainless Steel Frame

- This model is made for strapping on wet packages and in a high moisture environment.
- The frame and most of the parts are made of stainless steel such as screws and some hardware.
- The dispenser discs are made of ABS and equipped with rust-free patented Aluminum alloy made modular arch

#### Specifications

<b>Arch Size</b>	850W x 600H mm (Standard)
<b>Power Supply</b>	110/220V 50/60Hz 1Ph; 220/380V 50/60Hz 3 Ph;
<b>Strap Cycle Speed</b>	28 Cycles/60Hz, 26 cycles/50Hz per Min (It depends on the package size)
<b>Tension Strength</b>	Max. 70kg
<b>Strap Width</b>	6- 15.5mm
<b>Sealing Method</b>	Heat Sealing
<b>Dimensions</b>	1400W x 640D x 1475H mm
<b>Table Height</b>	810mm
<b>Machine Weight</b>	220kgs
<b>Gross Weight</b>	265kgs

**Categories:** [Fully Automatic Strapping System JN-85 Series](#), [Strapping Machine](#)



## SEMI-AUTO PALLET STRAPPING MACHINE JN-85 PSA

**SKU:** JN-85 PSA

**Semi-auto Pallet Strapping Machine JN-85 PSA**

**Semi-auto Pallet Strapping Machine with Mobile Strap Guide**

- Mobile Strap Guide
- Available for various products on pallet
- Dispenser core inner dia.: Ø200 mm (Standard)
- Mini. package height: H630 mm
- Available for PET strap (Optional)
- Available for Dispenser core inner dia.: Ø406 mm (Optional)

### Specifications

<b>Strap guide (Length)</b>	L 1000 mm (Standard)
<b>Power Supply</b>	110/220V 1 Phase; 220/380V/415V 3 Phase
<b>Dimension</b>	870W x 540D x 1380H mm
<b>Tension Strength</b>	Max. 70kg
<b>Strap Width</b>	12- 15 mm (Change kit and adjustment)
<b>Sealing Method</b>	Heat Sealing

**Categories:** [Fully Automatic Strapping System JN-85 Series](#), [Strapping Machine](#)



## FULLY AUTOMATIC STRAPPING SYSTEM JN-85 ZE

**SKU:** JN-85 ZE

### Fully Automatic Strapping System JN-85 ZE

#### Outside Tension Model

- Outside Tension Adjustment: it is easy to adjust the tension via Tension Knob.
- Automatic positioning and re-try functions: to secure the strap goes to its proper position and every cycle is accurate and efficient.
- Fully Automatic Strapping System JN-85 ZE is controlled by P.C. Board with multiple functions.
- ABS Dispenser. (Optional)
- Basic functions are the same as JN-85E.
- With CKD frame and powder painting on a frame.
- Change color on the iron arch cover, front doors & frame is available.(Optional)

#### Specifications



<b>Arch Size</b>	850W x 600H mm (Standard) (Aluminum arc cover)
<b>Power Supply</b>	110/220V 1 Phase; 220/380V/415V 3 Phase
<b>Strap Cycle Speed</b>	28-30 Cycles / Min. (60Hz) (It depends on the package size)
<b>Tension Strength</b>	Max. 70kg
<b>Strap Width</b>	6- 15 mm (Change kits and adjustment)
<b>Sealing Method</b>	Heat Sealing
<b>Dimensions</b>	1400W x 640D x 1475H mm (Standard)
<b>Table Height</b>	810mm
<b>Machine Weight</b>	220kgs
<b>Available Packing Size</b>	100-825W x 30-580H mm

**Categories:** [Fully Automatic Strapping System JN-85 Series](#), [Strapping Machine](#)



**QUICK 3PL**

LOGISTICS SIMPLIFIED



**QUICK 3PL**

LOGISTICS SIMPLIFIED



## FULLY AUTOMATIC STRAPPING SYSTEM JN-85 E

**SKU:** JN-85 E

### Fully Automatic Strapping System JN-85 E

#### Standard Model

- Modular designed Aluminum alloy arch, easy to assemble and disassemble.
- Auto strap positioning and retry feeding functions enable the operation of humanity.
- Convenient operating modes with panel, ball switch and foot pedal switch.
- Internal electricity is 24V accessible, preventing operators from shocking.
- With CKD frame and powder painting on frame. Change color on the iron arch cover, front doors & frame is available. (Optional)

#### Specifications



<b>Arch Size</b>	850W x 600H mm (Optional)
<b>Power Supply</b>	110/220V 50/60Hz 1Ph; 220/380V 50/60Hz 3Ph
<b>Strap Cycle Speed</b>	28 Cycles 60Hz, 26 cycles/ 50Hz per Min
<b>Tension Strength</b>	Max. 70kgs
<b>Strap Width</b>	6- 15.5mm
<b>Sealing Method</b>	Heat Sealing
<b>Dimensions</b>	1400W x 640D x 1475H mm
<b>Table Height</b>	810mm
<b>Machine Weight</b>	220kgs
<b>Gross Weight</b>	265kgs

**Categories:** [Fully Automatic Strapping System JN-85 Series](#), [Strapping Machine](#)



**QUICK 3PL**

LOGISTICS SIMPLIFIED



**QUICK 3PL**

LOGISTICS SIMPLIFIED



## FULLY AUTOMATIC STRAPPING SYSTEM JN-85 PBAPN

**SKU:** JN-85 PBAPN

**Fully Automatic Strapping System JN-85 PBAPN**

### Pre-arrange, positioning Functions Enclosed

- Accessed in Magazines or Catalogs publishing line, which is suitable for strapping on the printed catalogs or papers with pre-arranging and pressing bar.
- In order to fit with various-sized publications, this system can be adjusted for different strapping positions.
- This system is usually incorporated with the transporting and strapping of publications before binding is complete.



### Specifications

<b>Arch Size</b>	650W x 400H mm (Optional)
<b>Power Supply</b>	110/220V 50/60Hz 1Ph; 220/380V 50/60Hz 3Ph
<b>Tension Strength</b>	Max. 70kgs
<b>Strap Width</b>	6- 15.5mm
<b>Sealing Method</b>	Heat Sealing
<b>Cylinder</b>	Inner Diameter. 040
<b>Pressure</b>	5kg/cm2 (Bar)
<b>Table Height</b>	825mm
<b>Max Packing Size</b>	300W x 350H mm
<b>Min Packing Size</b>	120W x 100H mm.

**Categories:** [Fully Automatic Strapping System JN-85 Series](#), [Strapping Machine](#)



## FULLY AUTOMATIC STRAPPING MACHINE – JN-85 PBTAPN

**SKU:** N/A

### Fully Automatic Strapping Machine – JN-85 PBTAPN

Power Belt Table with Light-Duty Air Pressure

- Suitable for bigger carton/paperboard or pre-transported forming-case strapping
- Fully Automatic Strapping Machine is equipped with 2 sets of photocell and light-duty air-pressing bar.
- Refer to JN-85PRAPN for the rest of the features.
- With Red /Yellow ? Green Warning Lamp & Buzzer

### Specifications

<b>Action Size</b>	1050W x 600H mm (Optional)
<b>Power Supply</b>	110/220V 50/60Hz 1Ph; 220/380V 50/60Hz 3Ph
<b>Strap Width</b>	9 – 15.5mm
<b>Sealing Method</b>	Heat Sealing
<b>Cylinder</b>	Inner Diameter. 040
<b>Pressure</b>	5kg/cm2 (Bar)
<b>Stroke</b>	550mm
<b>Table Height</b>	815mm
<b>Max Packing Size</b>	1000W x 560H mm
<b>Min Packing Size</b>	300W x 100H mm

**Categories:** [Fully Automatic Strapping System JN-85 Series](#), [Strapping Machine](#)



**QUICK 3PL**  
LOGISTICS SIMPLIFIED



**QUICK 3PL**  
LOGISTICS SIMPLIFIED



## INDEX

### F

- Fully Automatic Strapping Machine - JN-85 PBTAPN 19
- Fully Automatic Strapping System JN-85 APN 1
- Fully Automatic Strapping System JN-85 E 16
- Fully Automatic Strapping System JN-85 EM 9
- Fully Automatic Strapping System JN-85 LPBU 6
- Fully Automatic Strapping System JN-85 LPRU 8
- Fully Automatic Strapping System JN-85 OP 3
- Fully Automatic Strapping System JN-85 PBAPN 18
- Fully Automatic Strapping System JN-85 PBU 7
- Fully Automatic Strapping System JN-85 PRAPN 4
- Fully Automatic Strapping System JN-85 PRU 5
- Fully Automatic Strapping System JN-85 SE 12
- Fully Automatic Strapping System JN-85 ZE 14

### S

- Semi-auto Pallet Strapping Machine JN-85 PSA 13
- Semi-automatic pallet strapping machine JN-85 PS 11

