



## TABLE OF CONTENTS

<b>Fully Automatic Strapping Machine JNY-85 Series</b> .....	2
Fully Automatic Strapping Machine JN-85Y UDH with Double Sealing Head .....	2
Fully Automatic Strapping Machine JN-85Y S-2HT .....	4
Fully Automatic Strapping Machine JN-85Y U Big Arch Model .....	5
Fully Automatic Strapping Machine JN-85Y U-4HT .....	6
Fully Automatic Strapping Machine JN-85Y RS .....	7
Fully Automatic Strapping Machine JN-85Y U .....	8
Fully Automatic Strapping Machine JN-85 PPRAP .....	9
Fully Automatic Strapping Machine JN-85 WHM .....	11






# FULLY AUTOMATIC STRAPPING MACHINE JNY-85 SERIES

## FULLY AUTOMATIC STRAPPING MACHINE JN-85Y UDH WITH DOUBLE SEALING HEAD

**SKU:** JN-85Y UDH

### Fully Automatic Strapping Machine JN-85Y UDH with Double Sealing Head



- Basic functions are the same as the side sealing machine of JN-85YU Big Arch Model, but are equipped with Double Sealing Heads for customer special requirements.
- The machine can be redesigned and installed underground. (Optional)
- Fully Automatic Strapping Machine JN-85Y UDH is equipped with free roller conveyors or customer's power driving (roller) conveyors, etc. (Optional)
- Iron Arch Cover and corner stabilizers will be used for this special machine for arch stability and safety reasons.
- Dispenser core inner diameter: Ø406 mm (Better)

### Specifications

<b>Arch Size</b>	<b>1600W x 2800H mm (Iron Cover Arch)</b>
<b>Power Supply</b>	<b>220V/380V/415V 3 Phase</b>
<b>Strap Cycle Speed</b>	<b>22-25 Cycles/Min. (50HZ) (It depends on the package size)</b>
<b>Tension Strength</b>	<b>Max. 70 kg</b>
<b>Dimensions</b>	<b>3125W x 1140D x 2995H mm</b>
<b>Strap Width</b>	<b>15 or 19 mm (Change kits and adjustments)</b>
<b>Sealing Method</b>	Heat Sealing
<b>Max Packing Size</b>	

**Categories:** [Fully Automatic Strapping Machine JNY-85 Series](#), [Strapping Machine](#)



**QUICK 3PL**

LOGISTICS SIMPLIFIED



**QUICK 3PL**

LOGISTICS SIMPLIFIED



## FULLY AUTOMATIC STRAPPING MACHINE JN-85Y S-2HT

**SKU:** JN-85Y S-2HT

### Fully Automatic Strapping Machine JN-85Y S-2HT with 2 photocells



- Machine frame and most of the parts & accessories are made of stainless steel.
- Equipped with an IP66 approved ABS control box (i.e. waterproof, dustproof, acid-proof and alkali-proof)
- Electricity leakage breaker protected main-power switch on control panel.
- Connected with the user's power driving (rollers) conveyors. (Optional)
- Fully Automatic Strapping Machine JN-85Y S-2HT is suitable for strapping seafood, frozen food or food strapping systems, etc.
- Optional installation for different needs:
- Fully Automatic Strapping Machine JN-85Y S-2HT has a stainless Steel Arch
- Stainless Steel Castors
- Internal lamp to keep cabinet dry

### Specifications

<b>Arch Size</b>	<b>600W x 1050H mm (Aluminium Arch) (Optional Stainless Steel Arch)</b>
<b>Power Supply</b>	<b>110/220V 50/60Hz 1Ph, 220V/380V/415V 50/60Hz 3 Ph;</b>
<b>Strap Cycle Speed</b>	<b>26 Cycles/Min. (60HZ) (It depends on the package size)</b>
<b>Tension Strength</b>	<b>Max. 70 kg</b>
<b>Dimensions</b>	<b>1395W x 640D x H mm</b>
<b>Strap Width</b>	<b>9-15 mm (Change kits and adjustment)</b>
<b>Sealing Method</b>	Heat Sealing
<b>Max Packing Size</b>	

**Categories:** [Fully Automatic Strapping Machine JNY-85 Series](#), [Strapping Machine](#)



## FULLY AUTOMATIC STRAPPING MACHINE JN-85Y U BIG ARCH MODEL

SKU: N/A

### Fully Automatic Strapping Machine JN-85Y U Big Arch Model



- Basic functions are the same as the standard model. (Refer to Standard Model)
- If the arch size is larger than standard by total 1000 mm, then to be equipped with an additional sub-pool box is necessary.
- Connected with free roller tables or power roller conveyors is optional equipment.
- Iron Arch Cover and corner stabilizers will be used for a big arch for arch stability and safety reasons.
- Fully Automatic Strapping Machine JN-85Y U is equipped with an "Arch Strap Guide" to stabilize the P.P. strap to its proper position.
- P.E.T. strap strapping system is available and optional.
- Dispenser core inner diameter: Ø406 mm. (Optional)

### Specifications

Arch Size	1200W x 2800H mm (Iron Cover Arch)(Optional)
Power Supply	110/220V 50/60Hz 1Ph, 220V/380V/415V 50/60Hz 3 Ph;
Strap Cycle Speed	3 Sec/Cycles (60HZ) (It depends on the package size)
Tension Strength	Max. 70 kg
Dimensions	2745W x 640D x 3365H mm
Strap Width	12, 15 or 19 mm
Sealing Method	Heat Sealing
Max Packing Size	

**Categories:** [Fully Automatic Strapping Machine JNY-85 Series](#), [Strapping Machine](#)



## FULLY AUTOMATIC STRAPPING MACHINE JN-85Y U-4HT

**SKU:** JN-85Y U-4HT

### Fully Automatic Strapping Machine JN-85Y U-4HT with Double Dispensers



- With double dispensers, it will save the users a lot of time on changing the P.P. strap coil.
- Available to connect with free roller conveyors or power roller conveyors to be a complete strapping line.
- The basic function of the machine is equipped with 2 photocells. (Option: with 3 photocells or 4 photocells, etc. It depends on the customers' requirements.)
- Fully Automatic Strapping Machine JN-85Y U-4HT is equipped with an "Arch Strap Guide" or "Brushes Set" to stabilize the P.P. strap to its proper position. (Optional)
- P.E.T. strap strapping system is available and optional. Dispenser core inner diameter: Ø 406 mm. (Optional)
- Red / Yellow / Green warning lamp and buzzer. (Optional)
- Iron arch cover and corner stabilizers will be used for a big arch for arch stability and safety reasons. (Optional)

### Specifications

<b>Arch Size</b>	<b>900W x 1350 mm (Aluminium arch cover)</b>
<b>Power Supply</b>	<b>110/220V/1 Phase, 220V/380V/415V 3 Phase</b>
<b>Strap Cycle Speed</b>	<b>3 Sec/Cycles (60HZ) (It depends on the package size)</b>
<b>Tension Strength</b>	<b>Max. 70 kg</b>
<b>Dimensions</b>	<b>1410W x 640D x 1810H mm</b>
<b>Strap Width</b>	<b>12 / 15 / 19 mm (Option)</b>
<b>Sealing Method</b>	Heat Sealing
<b>Max Packing Size</b>	1800W x 640D x 2165H mm

**Categories:** [Fully Automatic Strapping Machine JNY-85 Series](#), [Strapping Machine](#)



## FULLY AUTOMATIC STRAPPING MACHINE JN-85Y RS

**SKU:** JN-85Y RS

### Fully Automatic Strapping Machine JN-85Y RS with Free Roller Table



- Fully Automatic Strapping Machine JN-85Y RS's frame and most of the hardware are made of stainless steel. This model is rustproof and suitable for operating in damp areas or strapping wet packages.
- Accessing height height-adjustable ABS-free roller table (Between 585~685mm).
- Equipped with height-adjustable stainless steel stands (Max 100mm).
- Equipped with an IP-66 approved waterproof and dustproof ABS control box.
- Electricity leakage breaker protected main-power switch on the control panel, and an optional device installation of a lamp to keep the inner temperature and the machine interior dry

### Specifications



<b>Arch Size</b>	<b>600W x 630H mm (Standard)</b>
<b>Power Supply</b>	<b>110/220V 50/60Hz 1Ph; 220/380V 50/60Hz 3 Ph;</b>
<b>Strap Cycle Speed</b>	<b>28 Cycles /60 sec</b>
<b>Tension Strength</b>	<b>Max. 70 kg</b>
<b>Dimensions</b>	<b>1410W x 640D x 1810H mm</b>
<b>Strap Width</b>	<b>6-15 mm</b>
<b>Sealing Method</b>	Heat Sealing
<b>Table Height</b>	565-685mm
<b>Max Packing Size</b>	600W x 530-630H mm

**Categories:** [Fully Automatic Strapping Machine JNY-85 Series](#), [Strapping Machine](#)



- Optional Functions by Order Requests.
- Detection Function of Feeding Strap Position
- Indication Function of Feeding Strap Position
- Re-Feed Strap Function
- Control Voltage: 24 Volt

## FULLY AUTOMATIC STRAPPING MACHINE JN-85Y U

**SKU:** JN-85Y U

### Fully Automatic Strapping Machine JN-85Y U

#### Standard Model

- With indicating and detecting functions when forward feeding the strap positioning.
- The retry feeding of auto auto-correcting function to correct the failure strap.
- Safety internal control voltage: 24 volts. (Optional)
- All side-sealing models should note the minimum height of the packaging area
- Fully Automatic Strapping Machine JN-85Y U's side-sealing models can be equipped with a minimum of 2 photocells to cooperate with existing input and output conveyors with controlling circuitry, and the model will add -2HT in the end.

#### Specifications



<b>Arch Size</b>	<b>600W x 850H mm (Standard)</b>
<b>Power Supply</b>	<b>110/220V 50/60Hz 1Ph; 220/380V 50/60Hz 3 Ph;</b>
<b>Strap Cycle Speed</b>	<b>28 Cycles /60 sec</b>
<b>Tension Strength</b>	<b>Max. 70 kg</b>
<b>Dimensions</b>	<b>1400W x 640D x 1740H mm</b>
<b>Strap Width</b>	<b>9-15 mm</b>
<b>Sealing Method</b>	Heat Sealing
<b>Max Packing Size</b>	

**Categories:** [Strapping Machine](#), [Fully Automatic Strapping Machine JNY-85 Series](#)



## FULLY AUTOMATIC STRAPPING MACHINE JN-85 PPRAP

**SKU:** JN-85 PPRAP

### Fully Automatic Strapping Machine JN-85 PPRAP

#### With the wrapping machine

- The JN-85PPR is designed to strap pallets, and the Moveable Strap Guide will go through the pallet to complete the strapping purpose.
- Fully Automatic Strapping Machine JN-85 PPRAP is equipped with a movable side sealing head and 2 (two) photocells (Standard). The machine can be equipped with 3 (three) or 4 (four) photocells, which depend on the customer's requirements. (Optional).
- The side sealing and movable head stay close to the package to ensure a tight strapping effect.
- Fully Automatic Strapping Machine JN-85 PPRAP is equipped with a warning (3 color) lamp and a buzzer which alerts the operator of irregular situations such as the strap does not go to its proper position, trouble with strapping guide, etc.
- Can be connected with input conveyors, a 90-degree turntable, and output conveyors, etc. (Optional). It depends on customers' requirements. The design can be changed accordingly.
- Equipped with side Air Compression (Cylinder). (Optional)
- P.E.T., a strapping system, is available and optional.
- Dispenser core inner diameter: Ø 406 mm (Optional)

#### Specifications

<b>Arch Size</b>	<b>1300W x 2500H mm (Standard)</b>
<b>Power Supply</b>	<b>220V/380/415V 50/60Hz 3 Ph</b>
<b>Tension Strength</b>	<b>Max. 70 kg (Higher tensioning is an optional request)</b>
<b>Sealing Head Stroke</b>	<b>0-250 mm</b>
<b>Dimensions</b>	<b>1100W x 500H mm</b>
<b>Strap Width</b>	<b>12-19 mm</b>
<b>Sealing Method</b>	Heat Sealing
<b>Max Packing Size</b>	1120W x 1400L x 2400H mm

**Categories:** [Strapping Machine](#), [Fully Automatic Strapping Machine JNY-85 Series](#)



**QUICK 3PL**

LOGISTICS SIMPLIFIED



**QUICK 3PL**

LOGISTICS SIMPLIFIED



## FULLY AUTOMATIC STRAPPING MACHINE JN-85 WHM

**SKU:** JN-85 WHM

### Fully Automatic Strapping Machine JN-85 WHM



- New innovative design for horizontal strapping applications with chain-driven vertical movement.
- Fully Automatic Strapping Machine JN-85 WHM is equipped with 2 photocells (Standard). The machine can be equipped with 3 (three) or 4 (four) photocells, which depend on the customer's requirements. (Optional).
- Horizontal movable strapping head (100-200mm) can approach the package and tightly strap it.
- Exhaust of the strap detection function to notice by the warning lamp.(Optional).
- Incorrectly strapping the feeding detection function to the warning lamp. (Optional).
- The Arch Size is custom-made to user requirements.
- P.E.T. strapping system is available as an option.

### Specifications

<b>Arch Size</b>	<b>1250W x 1200H mm (Aluminium Arch)</b>
<b>Power Supply</b>	<b>220V/380/415V 50/60Hz 3 Ph</b>
<b>Tension Strength</b>	<b>Max. 70 kg</b>
<b>Sealing Head Stroke</b>	<b>1500 mm</b>
<b>Dimensions</b>	<b>1700W x 1080D x 2300H mm</b>
<b>Strap Width</b>	<b>9-19 mm</b>
<b>Sealing Method</b>	Heat Sealing
<b>Max Packing Size</b>	

**Categories:** [Fully Automatic Strapping Machine JNY-85 Series](#), [Strapping Machine](#)



**QUICK 3PL**

LOGISTICS SIMPLIFIED



**QUICK 3PL**

LOGISTICS SIMPLIFIED



## INDEX

### F

- Fully Automatic Strapping Machine JN-85 PPRAP 8
- Fully Automatic Strapping Machine JN-85 WHM 10
- Fully Automatic Strapping Machine JN-85Y RS 6
- Fully Automatic Strapping Machine JN-85Y S-2HT 3
- Fully Automatic Strapping Machine JN-85Y U 7
- Fully Automatic Strapping Machine JN-85Y U Big Arch Model 4
- Fully Automatic Strapping Machine JN-85Y U-4HT 5
- Fully Automatic Strapping Machine JN-85Y UDH with Double Sealing Head 1

